


BRU F45M/F45A 1000900/1000901	BRU F60M/F60A 1000902/1000903	DIMENSIONS
		
<ul style="list-style-type: none"> • 1.8 jug or 2.2 litre flask options • Manual and automatic fill options. 	<ul style="list-style-type: none"> • Improved sprayhead performance. • Simple set up, service and refurb 	

ENERGY-EFFICIENT AND EASY TO USE SMALL BATCH BREWERS FOR CANTEENS, COFFEE SHOPS, BUSINESSES OR CONFERENCES.

ASSOCIATED PRODUCTS (SOLD SEPARATELY)

REQUIRED
AIRPOT 2.2L (FOR BRU F60M/F60A) 1700179


ACCESSORIES

NAME ORDER CODE
2.2l Airpot 1700179
BRU Filter Papers - Case of 1000 8000200

NAME ORDER CODE	POWER @ 230V	BREW CAPACITY	DIMENSIONS (D x W x H mm)	PLUMBING REQS
F45M Jug Manual Fill 1000900	2.4kW	1.8 L	360 x 211 x 444	—
F45A Jug Auto Fill 1000901	2.4kW	1.8 L	360 x 211 x 444	3/4" BSP
F60M Flask Manual Fill 1000902	2.2kW	2.2 L	360 x 211 x 598	—
F60A Flask Auto Fill 1000903	2.2kW	2.2 L	360 x 211 x 598	3/4" BSP

BRU			
BRU F45M 1000900	BRU F45A 1000901	BRU F60M 1000902	BRU F60A 1000903
<p>PLUMBING INSTALLATION PROCEDURE</p> <ul style="list-style-type: none"> • Fit a stop valve and suitable fitting on a cold water line (e.g. 3/4" x 1/2" 311 or washing machine type stop valve). • The boiler requires a suitable food grade inlet hose with 3/4". • BSP female elbow fitting which will attach to the underside of the machine. • Make sure that the pre-attached sealing washer is fitted on both ends. • Turn on the water to flush any impurities, dust etc. from the inlet hose and water pipe. Allow several gallons through. 			
<ul style="list-style-type: none"> • Connect right-angled tailpiece of the hose to the inlet valve of the boiler (again 3/4" BSP). Make sure the sealing washer is fitted here again. • Turn on water and check for leaks. <p>NOTE: Using a non-food grade hose (e.g. a washing machine hose) will usually result in off-tastes & smells in the water, and can possibly be toxic.</p>			